6K28BS-U3T

Micro ATX Tower

Features

- Compliant with Micro ATX specifications
- 0.7mm steel processed in a highly stable and modern design
- double-crimped, deburred edges
- One side screwed drives for easy assembly
- two USB-ports and audio port in the front
- replaceable slot brackets
- enhanced slot-plates with EMI-protection
- lockable case
- Ventilation holes (TAC 2.0) for optimal CPU- and Graphics Cooling
- Optional: 1 x 8 or 9cm fan back
  Cage for 2x3,5“ HDD`s
  Toolless - Kit for 5,25“ and 3,5“ Drive assembly

similar to photo

Compucase Europe GmbH, Im Hülsenfeld 9, 40721 Hilden
Tel.: +49-2103-9881-0, Fax: +49-2103-9881-18, E-Mail: info@compucase.de

6K28BS-U3T

Micro ATX Tower

Specifications

Housing Type	Mini Tower
Series	6K-series
Dimensions with Front Bezel	430/180/375 mm (D/W/H)
Form Factor	Micro ATX
Housing Material	0.7 mm SECC - Steel
Weight	5.10 kg (6.45 kg Brutto)
Front Ports	2 x USB 3.0, HD Audio
Expansion Slots	4 Slots
Drive Space intern	1/2 x 3,5“ (8,89cm)
Drive Space extern	2 x 5,25” (13,34cm) / 2 x 3,5” (8,89cm)
Maximum Length of Graphics	up to 37cm
Ordering Stock Hilden	6K28BS-U3T

similar to photo

Compucase Europe GmbH, Im Hülsenfeld 9, 40721 Hilden
Tel.: +49-2103-9881-0, Fax: +49-2103-9881-18, E-Mail: info@compucase.de